

IN THE CLAIMS

Please amend the claims as follows:

1 (original). An integrated circuit including a power distribution system, the integrated circuit comprising:

a plurality of symmetrical power distribution structures associated with the power distribution system and distributed across at least a portion of a surface of the integrated circuit;

a plurality of circuit blocks coupled for receiving power through one or more of the plurality of power distribution structures; and

wherein:

- (a) each of the plurality of power distribution structures comprises:
 - (a1) a first power line for providing a first power supply voltage; and
 - (a2) a second power line and a third power line for providing a second supply voltage, wherein the second power line and the third power line are disposed symmetrically on opposite sides of the first power line;
- (b) the first power line and second power line are substantially parallel;
- (c) the second power line and the third power line each substantially has a width w and the first power line has a width equal to about twice the width w ; and
- (d) the plurality of power distribution structures are spaced substantially evenly across the portion of the surface.

2 (original). The integrated circuit of claim 1 wherein a first separation distance between the first power line and the second power line is about equal to a second separation distance between the first power line and the third power line.

3 (original). The integrated circuit of claim 1 wherein:

- (a) the plurality of circuit blocks comprises:

- (a1) a first circuit block; and
- (a2) a second circuit block that is substantially disposed as a mirror image of the first circuit block; and
- (b) a boundary of the first circuit block and a corresponding mirrored boundary of the second circuit block are offset a substantially equal distance from the plurality of power distribution structures.

4 (original). The integrated circuit of claim 3 wherein the first circuit block comprises a logic circuit.

5 (currently amended). An electronic device including a power distribution system, the electronic device comprising:

a plurality of substantially symmetrical power distribution structures associated with the power distribution system and distributed across at least a portion of a surface of the electronic device, wherein each of the plurality of power distribution structures comprises a first power line, a second power line, and a third power line; ~~and~~

a plurality of circuit blocks coupled for receiving power through one or more of the plurality of power distribution structures; ~~and~~
wherein:

the first power line provides a first power supply voltage;

the second power line and the third power line provide a second supply voltage;

the second power line and the third power line are disposed substantially symmetrically on opposite sides of the first power line; and

the first power line has a width greater than the width of each of the second power line and the third power line.

6 (currently amended). The electronic device of claim 5 wherein each of the plurality of power distribution structures is a triplet structure and the plurality of power distribution structures is spaced with a substantially constant pitch.:

~~the first power line provides a first power supply voltage; and~~

~~the second power line and the third power line provide a second supply voltage, wherein the second power line and the third power line are disposed substantially symmetrically on opposite sides of the first power line.~~

7 (currently amended). The electronic device of claim 56 wherein the first power line and second power line are substantially parallel.

8 (currently amended). The electronic device of claim 56 wherein:
the second power line and the third power line each substantially has a width w ; and
the first power line has a width equal to about twice the width w .

9 (original). The electronic device of claim 8 wherein a first separation distance between the first power line and the second power line is about equal to a second separation distance between the first power line and the third power line.

10 (original). The electronic device of claim 7 wherein the plurality of power distribution structures are spaced substantially evenly across the portion of the surface.

11 (currently amended). The electronic device of claim 56 wherein:
the first power supply voltage is a ground voltage; and
the second power supply voltage is a positive voltage relative to the ground voltage.

12 (original). The electronic device of claim 11 further comprising:
a first power supply voltage pad disposed substantially at the surface of the electronic device and electrically coupled to at least one of the plurality of power distribution structures;
and
a second power supply voltage pad disposed substantially at the surface of the electronic device and electrically coupled to at least one of the plurality of power distribution structures.

13 (original). The electronic device of claim 12 wherein the electronic device is an integrated circuit chip and further comprising a power distribution ring, disposed around a substantial portion of the perimeter of the integrated circuit chip, electrically coupled to the first power supply voltage pad and to the plurality of power distribution structures.

14 (original). The electronic device of claim 12 wherein the first power supply voltage pad corresponds to the ground voltage and the second power supply voltage pad corresponds to the positive voltage.

15 (original). The electronic device of claim 5 wherein the electronic device is selected from the group consisting of:

- an integrated circuit; and
- a printed circuit board assembly.

16 (original). The electronic device of claim 5 wherein the plurality of circuit blocks is selected from the group consisting of:

- a plurality of semiconductor chips mounted on a printed circuit board, wherein each of the semiconductor chips comprises a transistor; and
- a plurality of transistor circuits disposed in an integrated circuit.

17 (currently amended). The electronic device of claim 5 wherein the plurality of circuit blocks comprises:

- a first circuit block; and
- a second circuit block that is substantially ~~disposed as a~~ mirror image of the first circuit block.

18 (original). The electronic device of claim 17 wherein a boundary of the first circuit block and a corresponding mirrored boundary of the second circuit block are offset a substantially equal distance from the plurality of power distribution structures.

19 (original). The electronic device of claim 18 wherein the first circuit block comprises a logic circuit.

Claims 20 - 24 (canceled)

25 (original). A power distribution structure for providing power supply voltages to a plurality of circuit blocks in an integrated circuit, the power distribution structure comprising:

- a first power line having a width w to provide a first power supply voltage to the plurality of circuit blocks;
- a second power line, having a width equal to about one-half of width w and running substantially parallel to the first power line, to provide a second power supply voltage to at least a portion of the plurality of circuit blocks;
- a third power line having a width substantially equal to about one-half of width w and running substantially parallel to the first power line and to the second power line, to provide the second power supply voltage to at least a portion of the plurality of circuit blocks; and

wherein the first power line, the second power line, and the third power line are symmetrically disposed about a center axis running substantially parallel to and inside the layout boundary of the first power line.

26 (original). The power distribution structure of claim 25 wherein the first power line and the second power line run substantially parallel for a distance of more than about 50 microns.

27 (original). The power distribution structure of claim 26 wherein a first separation distance between the first power line and the second power line is about equal to a second separation distance between the first power line and the third power line

28 (original). The power distribution structure of claim 25 wherein:

- the first power line is electrically coupled to a first circuit block of the plurality of circuit blocks; and

the second power line is electrically coupled to the first circuit block.

29 (original). The power distribution structure of claim 28 wherein a substantially linear side of the perimeter of the first circuit block runs substantially parallel to the first power line for a distance of more than about 50 microns.

30 (original). An integrated circuit comprising:
a master circuit block layout;
an image circuit block layout;
a power distribution system comprising a first power distribution structure running substantially across the master circuit block layout and a second power distribution structure running substantially across the image circuit block layout; and

wherein:

(i) the first and second power distribution structures are each substantially symmetrical about a central axis, substantially the same in shape, and each coupled to the power distribution system to provide first and second power supply voltages to the master and image circuit block layouts;

(ii) the image circuit block layout has a substantially identical layout to the master circuit block layout; and

(iii) the layout positions of the first and second power distribution structures relative to the corresponding master and image circuit block layouts is substantially symmetrical about a symmetry axis located between the master and image circuit block layouts.

31 (original). The integrated circuit of claim 30 wherein the first and second power distribution structures each comprises:

a first power line having a width w to provide the first power supply voltage to the master and image circuit block layouts;

a second power line, having a width equal to about one-half of width w and running substantially parallel to the first power line, to provide the second power supply voltage to the master and image circuit block layouts;

a third power line having a width substantially equal to about one-half of width w and running substantially parallel to the first power line and to the second power line, to provide the second power supply voltage; and

wherein the first power line, the second power line, and the third power line are symmetrically disposed about the central axis.

32 (new). The integrated circuit of claim 30 wherein the first and second power distribution structures each comprises a first power line, a second power line, and a third power line and each of the first, second and third power lines is symmetrically disposed about the central axis.

33 (new). The integrated circuit of claim 30 wherein the first and second power distribution structures each comprises:

a first power line having a width w to provide the first power supply voltage to the master and image circuit block layouts; and

a second power line, having a width less than width w and running substantially parallel to the first power line, to provide the second power supply voltage to the master and image circuit block layouts.

34 (new). The integrated circuit of claim 33 wherein the first and second power distribution structures each further comprises:

a third power line having a width less than width w and running substantially parallel to the first power line and to the second power line, to provide the second power supply voltage; and

wherein the first power line, the second power line, and the third power line are symmetrically disposed about the central axis.

35 (new). An electronic device including a power distribution system, the electronic device comprising:

a plurality of substantially symmetrical triplet structures repeated across at least a portion of a surface of the electronic device, wherein each of the plurality of triplet structures comprises a first power line, a second power line, and a third power line and wherein the triplet structures are spaced with a substantially constant pitch; and

a plurality of circuit blocks coupled for receiving power through one or more of the plurality of power distribution structures.

36 (new). An electronic device including a power distribution system, the electronic device comprising:

a plurality of substantially symmetrical power distribution structures distributed across at least a portion of a surface of the electronic device, wherein each of the plurality of power distribution structures comprises a first power line, a second power line, and a third power line;

a plurality of circuit blocks coupled for receiving power through one or more of the plurality of power distribution structures; and

wherein:

the first power line provides a first power supply voltage;

the second power line and the third power line provide a second supply voltage;

the second power line and the third power line are disposed substantially symmetrically on opposite sides of the first power line;

the second power line and the third power line each substantially has a width w ;

and

the first power line has a width equal to about twice the width w .

37 (new). The electronic device of claim 36 wherein a first separation distance between the first power line and the second power line is about equal to a second separation distance between the first power line and the third power line.

38 (new). An electronic device including a power distribution system, the electronic device comprising:

a plurality of substantially symmetrical power distribution structures associated with the power distribution system and distributed across at least a portion of a surface of the electronic device, wherein each of the plurality of power distribution structures comprises a first power line, a second power line, and a third power line;

a plurality of circuit blocks coupled for receiving power through one or more of the plurality of power distribution structures; and

wherein the plurality of circuit blocks comprises:

a first circuit block; and

a second circuit block that is substantially a mirror image of the first circuit block.

39 (new). The electronic device of claim 38 wherein a boundary of the first circuit block and a corresponding mirrored boundary of the second circuit block are offset a substantially equal distance from the plurality of power distribution structures.

40 (new). The electronic device of claim 39 wherein the first circuit block comprises a logic circuit.